



Advantage

- UL and LightingFacts Certified
- High lumen efficiency, more than 100lm/w
- High CRI, more than 80Ra
- 5 Year Warranty

Technical Data

| | | | |
|--------------------------------|-------------------|-----------------------|-----------------------|
| Color Temperature (K) | 3000K to 5000K | Input Voltage | 100-277VAC/100-347VAC |
| Beam Angle | 120 Degree | Frequency (Hz) | 50/60 |
| Color Consistency | 4 Steps | Power Factor | > 0.99 |
| Color Render Index (Ra) | > 80 | Rated Life | 50,000Hours |
| Operation Temperature | -22F - 104F | LED Type | SMT 2835 |
| Housing Plastic | Aluminium/Plastic | Warranty | 5 Years |

Specification

| Product code | Length | Housing | Certification | Input Voltage | Description | | Lumens | Packing/carton |
|-----------------------------|--------|---------------|---------------------------|---------------|-------------|----------|---------|----------------------|
| | | | | | CRI | Driver | | |
| ZY-T8P-10W900 BINS LED TUBE | 3 ft | Whole Plastic | UL,cUL and Lighting Facts | AC100-277V | >80 | Internal | 1150 lm | 37.4x8.7x9.8in 30PCs |
| ZY-T8-10W900 BINS LED TUBE | 3 ft | Aluminium | UL,cUL and Lighting Facts | AC100-277V | >80 | Internal | 1150 lm | 37.4x8.7x9.8in 30PCs |
| ZY-T8-10W900 BINS LED TUBE | 3 ft | Aluminium | UL,Cul and Lighting Facts | AC100-347V | >80 | Internal | 1150 lm | 37.4x8.7x9.8in 30PCs |

Ordering Guide

| ZY | T5/T8/T8P | 13W/15W/18W/20W | 600-2400 | B | I/O | XY |
|--------------|--|-----------------|--|----------|--|--|
| Company Code | Housing Type T5/T8: Aluminium T8P: Plastic | Wattage | Length 600(2ft) 900(3ft) 1200(4ft) 1500(5ft) 1800(6ft) 2400(8ft) 600U(2ft,U Tube) | 2835 Led | I: Internal Driver O: External Driver | Input Type X: N(Non dimmable) D(Dimmable) Y: T(Double end input) S(Single end input) |