



Advantage

- UL and LightingFacts Certified
- High lumen efficiency, more than 100 lumen/w
- High CRI, more than 80Ra
- 5 Year Warranty

Technical Data

Color Temperature (K)	3000K to 5000K	Input Voltage	100-277VAC/100-347VAC
Beam Angle	120 Degree	Frequency (Hz)	50/60
Color Consistency	4 Steps	Power Factor	> 0.99
Color Render Index (Ra)	> 80	Rated Life	50,000Hours
Operation Temperature	-22F - 104F	LED Type	SMT 2835
Housing Plastic	Aluminium	Warranty	5 Years

Specification

Product code	Length	Housing	Certification	Input Voltage	Description		Lumens	Packing/carton
					CRI	Driver		
ZY-T8-22W1500 BINS LED TUBE	5 ft	Aluminium	UL,cUL,DLC V2.1 and Lighting Facts	AC100-277V	>80	Internal	2640 lm	61.4x8.7x9.8in 30PCs
ZY-T8-22W1500 BINS LED TUBE	5 ft	Aluminium	UL,Cul and Lighting Facts	AC100-347V	>80	Internal	2640 lm	61.4x8.7x9.8in 30PCs

Ordering Guide

ZY	T5/T8/T8P	13W/15W/18W/20W	600-2400	B	I/O	XY
Company Code	Housing Type	Wattage	Length	2835 Led	I: Internal Driver O: External Driver	Input Type
	T5/T8: Aluminium T8P: Plastic		600(2ft) 900(3ft) 1200(4ft) 1500(5ft) 1800(6ft) 2400(8ft) 600U(2ft,U Tube)			X: N(Non dimmable) D(Dimmable) Y: T(Double end input) S(Single end input)