



### Advantage

- UL and LightingFacts Certified
- High lumen efficiency, more than 100lumen/w
- High CRI, more than 80Ra
- 5 Year Warranty

### Technical Data

<b>Color Temperature (K)</b>	3000K to 5000K	<b>Input Voltage</b>	100-277VAC/100-347VAC
<b>Beam Angle</b>	120 Degree	<b>Frequency (Hz)</b>	50/60
<b>Color Consistency</b>	4 Steps	<b>Power Factor</b>	> 0.99
<b>Color Render Index (Ra)</b>	> 80	<b>Rated Life</b>	50,000Hours
<b>Operation Temperature</b>	-22F - 104F	<b>LED Type</b>	SMT 2835
<b>Housing Plastic</b>	Aluminium	<b>Warranty</b>	5 Years

### Specification

Product code	Length	Housing	Certification	Input Voltage	Description		Lumens	Packing/carton
					CRI	Driver		
ZY-T8-31W2400 BINT LED TUBE	8 ft	Aluminium	UL,cUL and Lighting Facts	AC100-277V	>80	Internal	3720 lm	96.9x8.7x7.9in 10PCs
ZY-T8-40W2400 BINT LED TUBE	8 ft	Aluminium	UL,cUL and Lighting Facts	AC100-277V	>80	Internal	4800 lm	96.9x8.7x7.9in 10PCs
ZY-T8-30W2400 BINT LED TUBE	8 ft	Aluminium	UL,Cul and Lighting Facts	AC100-347V	>80	Internal	3600 lm	96.9x8.7x7.9in 10PCs

### Ordering Guide

ZY	T5/T8/T8P	13W/15W/18W/20W	600-2400	B	I/O	XY
Company Code	Housing Type T5/T8: Aluminium T8P: Plastic	Wattage	Length 600(2ft) 900(3ft) 1200(4ft) 1500(5ft) 1800(6ft) 2400(8ft) 600U(2ft,U Tube)	2835 Led	I: Internal Driver O: External Driver	Input Type X: N(Non dimmable) D(Dimmable) Y: T(Double end input) S(Single end input)