

2 Feet 22W T8 LED Tube with External Driver

Part No:

ZY-T8-22W1200 BONS (3000K Frosted)	ZY-T8-22W1200 BONS (3500K Frosted)	ZY-T8-22W1200 BONS (4000K Frosted)	ZY-T8-22W1200 BONS (4500K Frosted)	ZY-T8-22W1200 BONS (5000K Frosted)	ZY-T8-22W1200 BONS (5500K Frosted)	ZY-T8-22W1200 BONS (6000K Frosted)
ZY-T8-22W1200 BONS (3000K Clear)	ZY-T8-22W1200 BONS (3500K Clear)	ZY-T8-22W1200 BONS (4000K Clear)	ZY-T8-22W1200 BONS (4500K Clear)	ZY-T8-22W1200 BONS (5000K Clear)	ZY-T8-22W1200 BONS (5500K Clear)	ZY-T8-22W1200 BONS (6000K Clear)
ZY-T8-22W1200 BONT (3000K Frosted)	ZY-T8-22W1200 BONT (3500K Frosted)	ZY-T8-22W1200 BONT (4000K Frosted)	ZY-T8-22W1200 BONT (4500K Frosted)	ZY-T8-22W1200 BONT (5000K Frosted)	ZY-T8-22W1200 BONT (5500K Frosted)	ZY-T8-22W1200 BONT (6000K Frosted)
ZY-T8-22W1200 BONT (3000K Clear)	ZY-T8-22W1200 BONT (3500K Clear)	ZY-T8-22W1200 BONT (4000K Clear)	ZY-T8-22W1200 BONT (4500K Clear)	ZY-T8-22W1200 BONT (5000K Clear)	ZY-T8-22W1200 BONT (5500K Clear)	ZY-T8-22W1200 BONT (6000K Clear)
ZY-T8-22W1200 BODT (3000K Frosted)	ZY-T8-22W1200 BODT (3500K Frosted)	ZY-T8-22W1200 BODT (4000K Frosted)	ZY-T8-22W1200 BODT (4500K Frosted)	ZY-T8-22W1200 BODT (5000K Frosted)	ZY-T8-22W1200 BODT (5500K Frosted)	ZY-T8-22W1200 BODT (6000K Frosted)
ZY-T8-22W1200 BODT (3000K Clear)	ZY-T8-22W1200 BODT (3500K Clear)	ZY-T8-22W1200 BODT (4000K Clear)	ZY-T8-22W1200 BODT (4500K Clear)	ZY-T8-22W1200 BODT (5000K Clear)	ZY-T8-22W1200 BODT (5500K Clear)	ZY-T8-22W1200 BODT (6000K Clear)
ZY-T8-22W1200 BODS (3000K Frosted)	ZY-T8-22W1200 BODS (3500K Frosted)	ZY-T8-22W1200 BODS (4000K Frosted)	ZY-T8-22W1200 BODS (4500K Frosted)	ZY-T8-22W1200 BODS (5000K Frosted)	ZY-T8-22W1200 BODS (5500K Frosted)	ZY-T8-22W1200 BODS (6000K Frosted)
ZY-T8-22W1200 BODS (3000K Clear)	ZY-T8-22W1200 BODS (3500K Clear)	ZY-T8-22W1200 BODS (4000K Clear)	ZY-T8-22W1200 BODS (4500K Clear)	ZY-T8-22W1200 BODS (5000K Clear)	ZY-T8-22W1200 BODS (5500K Clear)	ZY-T8-22W1200 BODS (6000K Clear)



- 1,When you use our product ,please read the SPEC.
- 2, AC input voltage range subject to product equipment.
- 3,Before connection please confirm the working environment.
- 4,The SPEC just comply with this product.

Model No.		ZY-T8-22W1200 BOXX						
Rated Voltage		AC277-347VAC or AC100V-277V						
Rated working frequency		50-60HZ						
Rate power		23.5W MAX						
Power factor		0.90						
Type		External Driver, one driver for one tube and one driver for two tubes						
Size (mm)		φ1" x 2'						
Light source		SMD 2835 (132 pcs)						
Luminous flux (lm)	CCT	3000K±300K	3500K±300K	4000K±300K	4500K±300K	5000K±300K	5500K±300K	6000K±300K
	Min	>2300	>2300	>2350	>2350	>2400	>2450	>2450
	Typical	2300	2300	2350	2350	2400	2450	2450
Lumen maintenance	suggested environmental temperature	14F - 86F						
	Light on	8 hours/day						
	3 years	≥80%						
	L70 Life time	50000 hours						
CRI:Ra		≥80						
Location of power supply		One end connection and two ends connection						
UL Code		E358903 and E358956						
Beam angle		120°						
Thermal layer Material		6063 aluminum profile						
Certificates		UL,DLC,TUV MARK.SAA,C-TICK,ERP						
Warranty Period		5 years						
Weight		0.86lbs						
Storage conditions		Relative humidity < 85% of indoor air ventilation, should not have corrosive gas , storage temperature -4F - 112F						