



# STEC20/20G

## ILLUMINATION

- Long lasting, efficient ultra bright white LED lamp heads. 1.2 Watt per head.
- High performance chrome-plated metallized reflector and plastic lens for optimal light distribution.
- Adjustable LED lamp heads provides optimal center-to-center spacing.
- EXIT/RUNNING MAN SIGNS/SALIDA available.
- Long life, energy efficient.
- Optional Red or Green LED EXIT signs.
- Overload/Short Circuit Protection
- Single or double face (Universal).

## ELECTRICAL

- Dual 120/277 voltage available.
  - Charge rate/power "ON" LED indicator light and push-to -test. switch for mandated code compliance testing.
  - 3.6V Long life, maintenance-free, rechargeable Ni-Cd battery.
  - Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination.
  - Fully automatic solid-state, two rate charge initiates battery charging to recharge a discharged battery in 24 hours.

## MOUNTING

EZ-snap mounting canopy included for top or end mount. Universal K/O pattern on back plate for wall mount.

## HOUSING

Injection-molded, engineering grade. 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish. EZ snap-out chevron directional indicators.

## WARRANTY / LISTING

- Five year warranty on all electronics and housing. - Battery pro-rated for three years.
- meets UL 924
- cULus Listed for damp location(0°C-50°C)
- Life Safety NFPA 101
- NEC/OSHA
- T20, CEC/DOE
- Most State and Local Codes



## DIMENSIONS

