

QuadForce™ Tunable LED Half Cutoff Wall Pack

The QuadForce™ Tunable LED Half Cutoff Wall Pack, 125 lm/W, IP65 Wet Location, 0-10V Dimmable, Premium Outdoor Luminaire, Smart Sensor Ready.

Illuminate from dusk to dawn with QuadForce™ Tunable technology for 4X Wattages, Select (40W, 50W, 60W, 80W) or Select (90W, 100W, 110W, 120W).

Project:
Date:
Catalog No:
Prepared By:



FEATURES

Lumen Output	5000 to 15000 lumens
Efficacy	125 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
CCT	4000K, 5000K
IP Rating	IP65 Wet Location
Warranty	7 Years

APPLICATIONS

Premium outdoor luminaire suitable for wall mounting on building exteriors for entrances, courtyards, alleys, and pedestrian walkways.

CONSTRUCTION

Manufactured for weather-proof durability using solid heavy duty die cast aluminum housing with anti-UV polyester coating to resist water, salt, corrosion, discoloration, and scratching. IP65 Wet Location rated for dust-tight, water jets: IEC 60529.

ELECTRICAL

Input voltages 120-277V with 0-10V Continuous Dimming. Operating temperatures -22°F to 113°F (-30°C to 45°C). Surge Protection Rating L-N: 2kV, L/N-PE: 4kV: IEC 61000-4-5.

OPTICS

Anti-UV Clear Prismatic Tempered Glass Lens.

LISTINGS

DLC Premium listed. ETL certified to meet US and Canadian standards. FCC, CE and RoHS compliant.



WARRANTY

7 year exclusive limited warranty. View complete product warranty information

CORRELATED COLOR TEMPERATURES (CCT)

4000K



5000K



PHYSICAL DIMENSIONS

14.25"L x 7.56"W x 9.36"H

W



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V

Input Frequency: 50/60 Hz

Wattage: Select (40W, 50W, 60W, 80W), Select (90W, 100W, 110W, 120W)

Power Factor: >0.95

Operating Temperature: -22°F to 113°F (-30°C to 45°C)

LIGHTING DATA

Lumens: Select (5000, 6250, 7500, 10000), Select (11250, 12500, 13750, 15000)

Lumens Per Watt: 125 lm/W

Color Correlated Temperature (CCT): 4000K, 5000K

Dimmable: 1-10V

Color Rendering Index (CRI): >70

L70: 75000 hours

ORDERING INFORMATION

Model	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
ETH-TWP-80W-4000K	40W	120-277V	0.33A@120V, 0.14A@277V	5000	125 lm/W	5000K	0-10V	Dark Bronze	14.25"L x 7.56"W x 9.36"H
	50W		0.42A@120V, 0.18A@277V	6250					
	60W		0.50A@120V, 0.22A@277V	7500					
	80W		0.67A@120V, 0.29A@277V	10000					
ETH-TWP-80W-5000K	40W	120-277V	0.33A@120V, 0.14A@277V	5000	125 lm/W	5000K	0-10V	Dark Bronze	14.25"L x 7.56"W x 9.36"H
	50W		0.42A@120V, 0.18A@277V	6250					
	60W		0.50A@120V, 0.22A@277V	7500					
	80W		0.67A@120V, 0.29A@277V	10000					
ETH-TWP-120W-4000K	90W	120-277V	0.75A@120V, 0.32A@277V	11250	125 lm/W	5000K	0-10V	Dark Bronze	14.25"L x 7.56"W x 9.36"H
	100W		0.83A@120V, 0.36A@277V	12500					
	110W		0.92A@120V, 0.40A@277V	13750					
	120W		1.00A@120V, 0.43A@277V	15000					
ETH-TWP-120W-5000K	90W	120-277V	0.75A@120V, 0.32A@277V	11250	125 lm/W	5000K	0-10V	Dark Bronze	14.25"L x 7.56"W x 9.36"H
	100W		0.83A@120V, 0.36A@277V	12500					
	110W		0.92A@120V, 0.40A@277V	13750					
	120W		1.00A@120V, 0.43A@277V	15000					

ORDERING GUIDE

ETH	TWP	80W	5000K
ETH	Group	Wattage	CCT

SHIPPING INFORMATION

Model Wattage	Shipping Dimensions	Shipping Weight	Quantity /Box
All Models	14.96"L x 11.02"W x 9.45"D	11.46 lbs	1

ETH-TWP-120W-5000K

